CYLINDER SPEED GATE

MODEL: MT310



Product introduction

Cylinder speed gate offers a highs performance and high efficient method to ensure only authorized users are allowed access to each area of a building. The MT310 is high passing gate that is easily capable of handling high volume and abusive conditions. The compact unit makes it simple to deploy in a small space area. And nice design match perfectly to your lobby or branding.

The mechanism, controller, clutch, power supply and 12V power supply and servo motor are all integrated into one main post. This is an all-in-one machine. It is equiped with high end real servo motor which is stable and durable.


Elegance design of of robust 304 stainless steel body with transparent acrylic or tempered glass, the swing gate is ideal choice for the most demanding building entrances. With extra wide passage of a sinice pcs --900mm, this turnstile is comfortable and secure access to wheelchairs, large luggage or trollies. They have been carefully considered to ensure everyone – able and disabled have equally pleasing passage through out gates. (ADA access compliant passage width).




Technical Parameter

• Size	168*1050mm (141 Diameter option)
Material	2.0mm SUS 304
 Arm material 	10mm Acrylic ortempered glass
Pass Width	standard 600mm max 900mm(single pcs)
 Passage direction 	Single directional/Bi-directional
 Pass rate 	30-35 persons/minute
 Operating time 	0.2 seconds
 Power input 	AC100-240V,50/60HZ
 Working voltage 	24V
 Working humidity 	30%~95%
 Working temperature 	-40°C~+70°C
 Working environment 	outdoor
 Input interface 	RS485, Dry Contact Relay
 Mechanism 	DC servo motor
 Infrared sensor 	None
• MCBF	4,000,000 Cycles
 Feature 	LED on top
 Application 	Office Building, Hotels, Government Halls, etc

Dimension of Turnstile



Wiring diagram



Access Control System



Feature

LED alerts
LED on top. When standby, the LED is blue, when open, the LED turns to green. If encounter impact, the LED is red.

EMERGENCY EXIT
Functionality allows free passage in the event of an emergency or power ouage, au-

tomatic reset when power is restored.

WORKING DIRECTION
Single directional or Bi-directional is on

Single directional or Bi-directional is optional.

AUTOMATIC RESET

Arms will lock automatically within 5s (adjustable) if a person delay to access.

ANTI HIT MECHANISM

If some one hit the arm, it will open to some angle to release the force and reset automatically

SUPER MUTE The whole system runs smoothly and low noise

ARM OPTIONS LED is optional. Stainless steel arm is available.

FAST UNLOCK When there is a valid signal , the gate will unlock within 0.2s.

HIGH PERFORMANCE Long service life with low operational cost.

COMPACT DESIGN The cylinder speed gates are compact design. It is space efficient security barriers.

WIDE PASSAGE Wide passage is friendly for luggage, wheelchair acccess

ADVANTAGE 200w servo motor, precision metal gear planetary reducer, maintain a large torque, under high frequency use, the service life can reach 10 million times

Packaging









Packed in standard export wooden cases