# (MAIRS **SLIDING TURNSTILE MT247**

MT247 Sliding turnstiles move horizontally along a track or rail system. It opens and closes by sliding to the side, rather than swinging like a traditional hinged gate. Sliding turnstiles provide a higher level of security as they make it difficult to jump over or crawl under.

The automatic sliding turnstile gate provides bi-directional and unidirectional access control and free passage modes, In access control mode, upon receipt of a valid open signal from an access control system, the motorized barrier flap of the turnstile quickly retract into the cabinet, and the integrated sensors allow a single user to pass through the turnstile in the requested direction. If an unauthorized user attempts to tailgate on the entry, the unit will recognize the illegal passage, a violation alarm (with user configurable sounds) will sound. At the same time, a special fire control interface is equipped in the system to meet the requirement of fire control passage, so that a rapid down rod control may be realized when emergency. We can also make it to be ADA lane for handicapped or luggage access.















PASSING SPEED

PASSAGE FOR DISABLE

**BI-DIRECTION** 

#### **Technical Specifications**

Dimension	1420*350*1000mm (4.66*1.15*3.28ft) (standard)
Passage Width	600mm (1.97ft)
Arm height (600mm passage width)	1200mm(3.94ft) above ground (Max 1500mm(4.92ft) )
Arm height (900mm passage width)	1200mm(3.94ft) above ground (Max 1500mm(4.92ft)) * The gate case will be widened and the swing arm can only be made of acrylic.
Pass Rate	35-45 person/min
Mechanism	Super Mute mechanism with DC brushed motor
IR sensor	6 pairs
Frame Material	SUS304
Sliding arm Material	Acrylic(standard), Tempered glass
Power Supply	100V-240V, 50/60Hz
Open Signal	Passive Relay (Dry Contact)
Communication	RS485
Working Direction	Bi-directional(standard), Unidirectional
Working Temperature	-35°C ∼ 60°C
Working Environment	Indoor

#### Relative Humidity

95% Maximum





- LED ALERTS Indicate traffic direction with highly-visible green and red X icons. It achieve real time displaying which improve the passing rate and convenient maintain.
- **EMERGENCY EXIT** The function allows free passage in the event of an emergency or power outage, automatic reset when power is restored.
- WORKING DIRECTION Single directional or Bidirectional is optional.
- AUTOMATIC RESET The arms will lock automatically within 5s (adjustable) if a person delay to access.
- **ANTI-PASS BACK** The gate will stay in lock if someone wants to entry in the reverse direction.
- ANTI-INTRUSION The gate is locked automatically until a valid open signal is sent.
- **FAST UNLOCK** One there is a valid signal, the gate will unlock within 0.2s (adjustable).
- HIGH PERFOMANCE Long-life performance, high operation dependability and fast response.
- HIGH MECHANISM Full height mechanism, running smoothly and stable
- ALARM FUNCTION Infrared sensor alarm function, in case of illegal intrusion and reverse intrusion.





## Customization

- Dimension: Can be made according to the client's site.
- Available max passage width can be 900mm (for wheelchairs and luggage).
- Sliding arm material available in acrylic or tempered glass.
- Material: 304 stainless steel to 316 stainless steel (wet environment), or iron with powder coated (color can be customized).
- Infrared sensors can be added.
- LED can be added on arms.
- Mounting base (for above floor wiring) and removable base (for temporary events) can be added.
- Cutouts can be customized to fit any reader.
- LOGO can be customized.
- Customized 3D drawings are available based on the site photos.
- OEM& ODM service is available.

> Please check with sales for customization fees.

#### Access control system

Our gates come with relay signals and RS485/RS232 interfaces. You can use your own access control system, or we can provide a complete access control system to you.



Remote control

QR code/ barcode



RFID card



Counter



Face recognition



Fingerprint recognition



Coin/Card collection



....

#### We also offer customization services.



Other frame colors available, RAL or RGB required.











Cutouts can be customized to fit any reader.





LOGO can be customized.



#### **Emergency mode**



Powered of equipment with Super Capacitor Backup



In case of a power outage, obstacles are unlocked and automatically open in the direction of egress.



Obstacles are locked in the open position so as not to interfere with the evacuation process.

## Lane combination







One lane

Two lanes







